

## GEP 710 Plus (600617000) Die grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600617000 EAN 4007430213532



Product may differ from Image



- Paddle switch with deadmans function: safe to operate due to an ergonomically integrated non-slip switch
- Long grinding spindle ideal for working on hard to reach places
- Spindle lock for simple change of tools
- Aluminium die-cast bearing flange for long service life of the machine
- Vario-Constamatic (VC)- Electronics for work with materials requiring customised speeds, which remain almost constant under load
- Thumbwheel for Speed Preselection
- Electronic safety shutdown of the motor for safe working in case the tool stops unexpectedly
- Restart protection: prevents unintentional start-up after power supply interruption
- Electronic overload protection for long service life
- Precise collar for stationary use
- Removable protective rubber cap for comfortable and safe working
- Slim design for ideal handling
- Precision collet for precise concentricity
- Metabo Marathon motor with patented dust protection for long service life



## Technical data

## Characteristics

| No-load speed                    | 10000 - 30500 rpm                     |
|----------------------------------|---------------------------------------|
|                                  | · · · · · · · · · · · · · · · · · · · |
| Rated input power                | 710 W                                 |
| Output power                     | 430 W                                 |
| Revolutions at rated load        | 24000 rpm                             |
| Collar diameter                  | 43 mm / 1 11/16 "                     |
| Collet chuck bore                | 6 mm / 0.2362 "                       |
| Weight (without power cable)     | 1.6 kg / 3.5 lbs                      |
| Cable length                     | 4 m / 13 ft                           |
| Vibration                        |                                       |
| Surface grinding (up to Ø 25 mm) | 5.6 m/s²                              |
| Uncertainty of measurement K     | 1.5 m/s <sup>2</sup>                  |
| Surface grinding (up to Ø 50 mm) | 16.9 m/s <sup>2</sup>                 |
| Uncertainty of measurement K     | 1.5 m/s <sup>2</sup>                  |
| Noise emission                   |                                       |
| Sound pressure level             | 80 dB(A)                              |
| Sound power level (LwA)          | 91 dB(A)                              |
| Uncertainty of measurement K     | 3 dB(A)                               |

## Scope of delivery

Collet 6 mm

Protective rubber cap

1 Open-jawed spanner